## Solid Surface Countertops -



## Solid Surface Countertops Data Sheet

Our **Solid Surface** countertops are ideal for kitchens, vanities and workstations for either residential, commercial or industrial applications where a hard wearing, durable counter with design appeal is required. These counters can be repaired from cracks, breakage and burns like new. Sanitation is improved with its seamless finish and ability to facilitate under counter mounted basins. Available in a wide range of colours, sizes and profiles, these counters are aesthetically pleasing and excellent value for money. Installation can be wall hung with brackets or on cabinets.



### Construction:

Solid Surface counters are made from high quality, 1/2" thick, solid surface sheets comprising of acrylic resins, fire-retardants and proprietary colouring agents, having a uniform colour throughout its thickness. Sheets are cut to size, sanded, glued with special colour matching adhesive, routed and finish sanded. There is a wide variety of colours, profiles and finishes to select from. Counters are furnished with a squaring strip to the back to accommodate inconsistent wall finishes.

### Sizes:

Solid Surface countertops are fully custom made to your exact location's unique size and characteristics. Templates of specific conditions are made on site for assisting in the fabrication process to match angles or other conditions. Typically fabricated and sold per square foot, each countertop is measured and priced independently based on level of difficulty, material and colour selected.



# Solid Surface Countertops – Solid Surface Countertops Data Sheet



# Profiles:

Below are the standard profiles offered by Pouchet for solid surface countertops.



## Support Brackets:

Where applicable, self-supporting or floating countertops can be supplied with mild steel, wall angle brackets, painted with red oxide primer. Based on the wall construction and countertop profile, there are brackets for masonry or drywall applications and a front apron reinforcing bracket. Masonry brackets are secured to the wall with expansion sleeve anchor bolts whereas drywall brackets use toggler bolts. Installed at recommended spacing, these brackets have been tested to exceed 168kg of force. Countertops and apron reinforcing brackets are then fastened from the underside with stainless steel self-tapping screws.



### Warranty:

**Solid Surface** countertops shall be free from defects in workmanship for a period of one (1) year from date of purchase. In the event of defects claim, a site visit will be arranged by a qualified technician, after which Neville C. Pouchet Limited will either repair or replace these components free of charge.

Neville C. Pouchet Limited reserves the right to, and does from time to time, make changes and improvements in design & specification. Rev: Solid Surface CT-11112021