



U696 One-way viewer - UL

- 150° angle of view
- For doors 1-3/8" to 2-1/16" thick
- Secure, tamper-resistant one-way thread installation
- Simple installation — only a 1/2" hole required
- Suggested installation height: 60" from floor

Material substrate

- Meets ANSI/BHMA A156.16, L23222
- UL listed 90 minute fire doors

Dimensions

- External diameter: 3/4"

Available accessory items

- Trim washer available, 3/4" x .032" thick.
- Extensions available for thicker doors
- Privacy viewer covers to prevent viewing from outside the room

Finishes

BHMA	Description	Substrate	Finish
606	Satin brass	Brass	B4
613	Oil rubbed bronze	Brass	B10B
619	Satin nickel	Brass	B15
622	Matte black	Brass	B-BLK
625	Bright chrome	Brass	B26
626	Satin chrome	Brass	B26D
---	Aged bronze	Brass	B-643e/716

For other colors, consult factory.



698 One-way wide angle viewer

U698 One-way wide angle viewer - UL

- 190° angle of view
- 4 optical glass lenses
- For doors 1-3/8" to 2-1/8" thick
- Simple installation — only a 9/16" hole required
- Suggested installation height: 60" from floor

Material substrate

- Meets ANSI/BHMA A156.16, L23222
- U698 is UL listed 90 minute fire doors

Dimensions

- External diameter: 1"
- Lens projects 1/4" from face of door

Available accessory items

- Extensions available for thicker doors
- Privacy viewer covers to prevent viewing from outside the room

Finishes

BHMA	Description	Substrate	Finish
605	Bright brass	Brass	B3
619*	Satin nickel	Brass	B15
622*	Matte black	Brass	B-BLK
625*	Bright chrome	Brass	B26
626	Satin chrome	Brass	B26D
---	Aged bronze	Brass	B-643e/716

*For other colors, consult factory. *Not available on 698.*

Hinges & pivots
A

Pulls & plates
B

Flush bolts & coordinators
C

Latches, catches & bolts
D

Stops
E

Exterior hardware
F5

Miscellaneous hardware
G