

# IVES® Aluminum geared hinges

**A34**

Hinges & pivots

**B**

Pulls & plates

**C**

Flush bolts & coordinators

**D**

Latches, catches & bolts

**E**

Stops

**F**

Exterior hardware

**G**

Miscellaneous hardware



## 157XY Full surface

- A patented easy-to-install, heavy duty, full surface continuous hinge
- Narrow Frame
- Patented center loaded, interlocking bearing design
- XY (lateral and vertical) adjustability while hanging the door
- Articulating cover design eliminates pinch point between center channel cover and door and frame leaf covers
- Non Handed for custom cut lengths
- 1/16" door inset
- 48" Maximum door width
- Beveled or square edge doors
- For doors weighing up to 550 lbs
- For lead-lined application consult factory for engineering specials

## Certifications

- Meets ANSI 156.26 for 150lbs and 300lbs
- UL10C certified

## Standard lengths

- 83", 95", 119"

## Standard mounting hardware

- 12-24 x 1/2" Steel self drilling / self tapping hex head screw

## Finishes

- Clear Anodized (US28), Dark Bronze Anodized (313AN), Black Anodized (315AN)

Custom anodizing and painting are available, consult factory.

## Options:

- HT.....Hospital tip
- EPT .....Electric power transfer
- TWP CON.....Electrical through wire panel with Allegion Connect

## Optional mounting hardware:

- TEKWD .....1/2 self drill, self tap 1/2 wood
- WD.....Wood door and frame

## For single door applications:

For pairs of doors see chart and general information

