

How to order Advantage louvers

Louvers

Example:

Model	Opening size	Finish	Options
4CY	1010	GY	SEC

Model

One-side security-mount (Comes with sheet metal screws)

4CY Vision-proof louver, steel, inverted "V", 20 g frame, 24 g blades - 1 3/4" doors

40Y Vision-proof louver, steel, inverted "V", 20 g frame, 24 g blades - transom any thickness

100AFL Vision-proof louver, fusible link, 16 g, 1 3/4" doors

700AA Vision-proof louver, aluminum, inverted "V", 1 3/8" - 2 1/4" doors (std. finish is ALF)

Thru-bolt mount (Comes with thru sex bolts)

XX4CY Vision-proof louver, inverted "V", 20 g frame, 24 g blades - 1 3/4" doors

XX700AA Vision-proof louver, aluminum, inverted "V", 1 3/4" doors, (std. finish is ALF)

Opening size (width x height)

Order by rough opening size.

Size is always 2 digits for width 2 digits for height - Example 8" x 8" would be 0808.

Finish

GY Grey

BG Beige

DB Dark bronze

(Note: 700AA and XX700AA available in standard aluminum silver powder coat only, ALF, no code required.)

(Note: 100AFL available in GY finish only. Specify GY when ordering.)

Special fasteners

SEC Security screws or security thru bolts