

Data Sheet

Rhino Series, Solid Core, Flush Doors



Rhino Series solid core flush doors are recommended for high traffic, interior use applications, such as main entrances. They are also suitable for private spaces, where privacy is paramount. Doors should be hung in steel frames within a masonry wall opening to support the weight. These doors are truly versatile as they may be painted or laminated in any colour and can be installed in any orientation.

Construction:

Doors shall comprise an externally constructed M.D.F. framing on edge, with vertical edges double layered for hinge and latch reinforcement. The internal core comprises a solid M.D.F. construction suitable for any hardware requirements. The core is concealed with 1/8" H.D.F. door skins, bonded under pressure using a spray applied contact adhesive. All edges are framed and trimmed flush with 1/2" thick hardwood and finish sanded. Doors are made to a finish thickness of either 1-5/8" or 1-3/4" depending the grade of hardware to be used.

Edge profile and material:

- Based on your design criteria and/or performance requirements, the door edge may be either "Exposed" OR "Concealed".
- The standard door edge is "Hardwood" but may be substituted with "Phenolic" for increased durability.

Finish options:

- *Prime painted* (all sides sanding sealed and prime painted white)
- *Laminated* (faces are laminate and edges finish sanded)

Warranty:

Rhino Series solid core flush doors shall be free from defects in material and workmanship for a period of one (1) year from date of purchase. This warranty does not cover damage due to negligence; vandalism; external use; water damage or shoddy installation. In the event of a potential defect, a site visit will be arranged with a qualified technician to inspect the door, after which Neville C. Pouchet Limited may either repair or replace the door free of charge.

